





Hello to the future of work

bility to help business diversify with times.



Apeos 3560/3060/2560

3560 35 ppm* ¹ 3060 30 ppm* ¹ 2560 25 ppm* ¹	2 sided Scanning 80ppm*2	1,200 × 1,200 dpi	7 inches	LED printhead EA-Eco LGK toner	
---	-----------------------------	-------------------	----------	-----------------------------------	--

•Wireless LAN Supported •Mobile Supported

*1: A4 LEF. *2: A4 LEF 200 dpi to Folder.

Uncompromising usability along with compatibility

Multipurpose device with small footprint and easy setup

- · Compact design with width of 590 x depth of 659 mm
- Select a right configuration of 1, 2 or 4 trays as per your growing requirements



2 tray configuration with its optimal height and adjustable UI makes it easy to operate for all (including people with special needs).

Shared machines for offices.

Increase to maximum paper capacity of 2,180 sheets*.


* 20lb. / 75 gsm paper, Standard + 3 Tray Module (optional).



Quick scanning of high-volume originals

- Up to 80 ppm can be read at high speed in Scan
- Up to 130 sheets can be loaded
- One pass DADF will not damage the original document
- Instantly scan without manual entry of each original size
- Automatically converts custom size originals to standard size





Uncompromising Image quality

- High-resolution printing of 1,200 x 1,200 dpi achieved with LED printhead
- Image Enhancement processing reproduces diagonal lines and the outlines of characters, which can become jagged when printed, more smoothly
- Achieved print that is eye-friendly and easy to scan by taking advantage of the low temperature fusing properties of EA-Eco LGK toner with lower glossiness

Quick startup and output for greater efficiency

- $\, \cdot \,$ Fast Boot Mode prepares the operation panel in 6 seconds *1
- · Quick warm up in less than 28 second
- First Copy Output Time in 4.5 seconds*²
- *1: Depending on the status of the main unit and configuration of options, it may not operate or take more than 6 seconds.
- *2: A4 LEF for Apeos 3560 when in horizontal/Monochrome preferred mode.

Direct scan to or print from USB for efficient operations

 You can directly print the documents stored on a USB flash drive or scanned data can be directly stored on a USB flash drive without using a PC





Quick and simple operability

Simple layout with easy navigation

Black and gray tone UI gives better contrast for easy recognition.

- · Icons are evenly spread for easy recognition
- · Consistent operation steps of each function for easy recall
- · Home screen personalisation for ease of access to commonly used functions
- Pin regular settings for registering frequent or repeated jobs
- · Clear visible light notifications for completed or error jobs
- · Subtle sound notification for alert and attention





Flexibility in office layout

Supports wireless LAN environment*1.

- Supports free addressing in the office with Wi-Fi support
- Up to five Wi-Fi Direct multifunction devices can be connected at the same time
- Supports direct mobile printing*2
- Print Utility, AirPrint, and Mopria® Print Service are supported
- *1: Optional.
- *2: When connecting to Wi-Fi Direct.

Smartphone becomes a "portable operation panel"

Seamless connectivity with mobile devices for Copy, Fax, Print, Scan*¹ jobs using the Print Utility*² application.

- Mobile device can be used as an alternative UI for operations control to minimise common touch points
- Frequent settings can be saved as "Favourites"
- Directly send fax or email with the addresses stored in the smartphone
- · Minimise printer touch points for hygiene reasons

Note: Connect to machine via wireless environment or Wi-Fi direct connection.

*1: E-mail, Scan to Folder.

*2: It can be downloaded free of charge from Google Play™ or App Store.



Various features saving time and effort in scanning operation

Scanned data can be transferred through a variety of methods including Email, URL, and send to PC (SMB/FTP/SFTP).

- Data can be sent by using multiple features simultaneously
- · Improve your digitalisation process with features including automatic orientation of scanned page to upright position, correcting the skewed page, or removing blank pages
- In addition to TIFF and JPEG, the scanned data can be converted to PDF with searchable OCR enabled

Safeguard important information

Information is an important asset which should be protected at all cost

Protect from unauthorised user

Multiple options of setting user authorisation allow administrator to select a right combination as per given environment.

- Local Authentication
- Authentication by Remote Server
- IC Card Authentication*
- User-specific feature access
- Private Charge Print
- * Optional

Additional layer of unwanted access can be created for specific users. (e.g. quests).

- Secondary Ethernet Kit*
- * Optional.

Protects Data

Protects against any malicious intent of hacking, tampering with device / system settings.

- Encryption of stored data
- Uses TPM* 2.0 chip for encryption key management
- Deletes settings and document information all at once
- * Trusted Platform Module

Protects the information by means of strong encryption while transferring it between devices, servers etc.

- Encryption of communication paths by SSL/TLS or IPsec
- Encryption when transferring via SMBv3 and SFTP
- Scan file encryption/signature
- Email encryption and signature by S/MIME
- TLS version limit
- · Elliptic curve cryptography
- WPA3

Protect from unauthorised access

Protects device settings at multiple levels by clearly demarking change restrictions for different target audience - End users, IT administrators and Service Engineers.

- Service representative operation restriction
- · Account lock to prevent unauthorised access
- · Information for changing the default password
- · Warnings displayed when using global IP address

Prevents unauthorised program from installing without notice. Robust IT audits are supported with device data logs for easy tracking.

- Software signature verification
- Remote update restrictions
- · IP address filtering
- Tampering detection at startup and automatic restoration when tampering is detected
- · Prevention of tampering during operation
- Audit log
- · Audit log system transfer

Prevents operation errors

Prevents information leakage due to inadvertent mistakes by administrators and users.

- · Scan documents to be delivered to fixed destination
- Re-enter fax recipient
- Annotations
- Watermark

Initiatives for environmental consideration



We are working to develop environmentally conscious products, including technologies that reduce the power consumption of multifunction devices and printers to achieve lower environmental impact.

Fujifilm Group introduced the certification program in which we clarify the environmental value of each product by assessments at the time of product development, conduct the evaluation based on our in-house certification criteria and certify the products* that are excellent in reducing environmental impact as "Green Value Products".

This product was certificated as a "Silver" rank product that reduces environmental impact at a higher level than industries'

This product was certificated as a "Silver" rank product that reduces environmental impact at a higher level than industries' standard.

* Products and services excellent in reducing environmental impact are those designed in consideration of environmental impact throughout their life cycle from acquisition of raw materials, production, usage, disposition, to reuse.

Initiatives for energy conservation

- Achieve both high image quality and energy conservation by equipping the LED printhead that enables space and energy saving design, as well as EA-Eco LGK toner that has low-temperature fusing performance
- Reduce the power consumption with the smart power saving feature that solely powers on the required parts according to the functions being used by customers

Initiatives for resources conservation

Functions contributing to paper consumption reduction
 Private Charge Print, Scan, Paperless Fax, Pages per Side/Multiple-Up etc.

Apeos 3560 / 3060 / 2560 **Functions & Specifications**

Basic Specifications / Copy Function

Item		3560	3060	2560	
Туре		Desktop / Console			
Memory capacity		4 GB (Max: 4 GB)			
Storage Device	e Capacity*1	128 GB			
Scan Resolution	on	600 x 600 dpi			
Printing Resol	ution	1,200 × 1,200 dpi			
Warm-up Time*2		[Embedded Plug-ins / Custom Services] *3 When enabled: 28 seconds or less (23 degrees Celsius room tempera- ture) When disabled: 22 seconds or less (23 degrees Celsius room tempera- ture)			
Recovery Time fro		14 seconds or less [AC 220 to 240 V model] (23 degrees Celsius room temperature)			
Original Size		Maximum of A3, 1	1 x 17", 297 x 432 mm fo	or both Sheet and Book	
	Max	A3, 11 x 17"			
Paper Size	Min	A5 [Postcard (100 x 148 mm), when using Bypass Tray]			
rapei size	Image loss width	Lead edge 4.0 mm, Trail edge 2.0 mm, Right/Left edge 2.0 mm			
Paper	Paper Tray	60 to 256 gsm			
Weight*4	Bypass Tray	60 to 216 gsm			
First Copy Out	put Time	4.5 sec. (A4 LEF)			
	A4 LEF / JIS B5 LEF	35 ppm	30 ppm	25 ppm	
Continuous	A4	26 ppm	23 ppm	19 ppm	
Copy Speed*5	JIS B5	13 ppm	13 ppm	11 ppm	
	JIS B4	22 ppm	20 ppm	16 ppm	
	A3	19 ppm	17 ppm	14 ppm	
	Standard	520 sheets x 1-tray + Bypass Tray 100 sheets			
Paper Tray Capacity*6	Optional	1 Tray Module: 520 sheets x 1-tray 3 Tray Module: 520 sheets x 3-tray			
	Max	2,180 sheets [Standard + 3 Tray Module]			
Output Tray Capacity*7		Upper Center: 250 sheets (A4 LEF), Lower Center: 250 sheets (A4 LEF)			
Power Supply		AC 220 to 240 V ±10%, 8A, 50/60 ±3% Hz common			
Maximum Power Consumption		1.76 kW or less (AC220V±10%) 1.92 kW or less (AC240V±10%) Sleep Mode: 0.4 or less, Ready Mode: 94 W or less (AC220 to 240 V model)			
Dimensions		$\label{eq:w590 x D 659 x H 768 mm / W 23.3 x D 26.0 x H 30.3"} W 590 x D 659 x H 881 mm / W 23.3 x D 26.0 x H 34.7" (When optional 1 Tray Module is installed.) W 590 x D 659 x H 1118 mm / W 23.3 x D 26.0 x H 44.1" (When optional 3 Tray Module is installed.)$			
Weight* ⁸		57 kg / 126lb. 67 kg / 148lb. (When optional 1 Tray Module is installed.) 82 kg / 181lb. (When optional 3 Tray Module is installed.)			

^{*1:} The Storage Device Capacity is not totally available for customers.

Print Function

Item		Description		
Туре		Built-in type		
Continuous Print Speed*1		Same as the Basic Specifications / Copy Function		
Printing Resolution	Standard	[PCL Driver] Standard: 600 x 600 dpi, High Resolution: 1,200 x 1,200 dpi		
	Optional	[Adobe® PostScript® 3™ Driver] Standard: 600 x 600 dpi, High Resolution: 1,200 x 1,200 dpi		
Page	Standard	PCL5 / PCL6		
Description Language	Optional	Adobe® PostScript® 3™		
Supported Operating System* ²	Standard	[PCL Driver] Windows 11 (64 bit), Windows 10 (32 bit / 64 bit), Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit), Windows Server 2012 R2 (64 bit), Windows Server 2012 (64 bit)		
		[Mac OS X Driver] macOS 13 / 12 / 11 / 10.15 / 10.14		
	Optional	[Adobe® PostScript® 3 TM Driver] Windows 11 (64 bit), Windows 10 (32 bit / 64 bit), Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit), Windows Server 2012 R2 (64 bit), Windows Server 2012 (64 bit) macOS 13 / 12 / 11 / 10.15 / 10.14		
Interface	Standard	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T, USB3.0		
	Optional	Wireless LAN (IEEE 802.11a / b / g / n / ac)		

^{*1:} The speed may be reduced due to the image quality adjustment. The printing speed may be reduced depending on the document.

Scan Function

Item		Description		
Туре		Color Scanner		
Scan Resolution		600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi		
Scan Speed		Same as the Scan Speed for the Duplex Automatic Document Feeder		
	Standard	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T		
Interface	Optional	Wireless LAN (IEEE 802.11a / b / g / n / ac)		

Fax Function (Optional)

Item	Description
Original Size	Max: A3, 11 x 17", Long document (Longest 600 mm / 23.7")
Recording Paper Size	Max: A3, 11 x 17"; Min: A5
Transmission Time	2 seconds and more but fewer than 3 seconds*
Transmission Mode	ITU-T G3
Applicable Lines	Telephone subscriber line, PBX, Fax communication (PSTN)

^{*}When A4 size document with approximately 700 characters is transmitted in standard image-quality (8 x 3.85 lines/mm) and in high-speed mode (28.8 kbps or faster, JBIG). Only indicates the time for transmitting the image information and does not include the communication control time. The total communication time will vary depending on the contents of the document, the type of machine receiving the fax, and line condition.

Duplex Automatic Document Feeder [1 pass, 2 sided scanning]

				_	
Item		3560	3060	2560	
Original Size / Paper Weight		Max: A3, 11 x 17"; Min: A6*1 38 to 128 gsm (In Duplex: 50 to 128 gsm)*2			
Capacity*3		130 sheets			
Scan Speed*4	Copy (A4 LEF, Simplex)	35 ppm	30 ppm	25 ppm	
	Scan	B/W: 80 ppm, Color: 80 ppm (1 pass, 2 sided scanning: B/W 80 ppm, Color 80 ppm) [Standard Document (A4 LEF), 200 dpj, to Folder.]			

^{*1:} The minimum custom size is 49×85 mm / 2.0 x 3.4".

^{*2:} It may change dependently is not change all the statements.

*3: Embedded Plug-ins / Custom Services are enabled as factory default. You can change the settings

^{*4:} It is recommended to use our recommended paper. Correct print output may not be possible depending on the requirement.

*5: The speed may be reduced due to the image quality adjustment.

^{*6: 20} lb. / 75 gsm paper.
*7: 70 gsm paper.
*8: Including Toner Cartridge.

^{*2:} Please refer to our official website for the latest supported OS.

^{*2:} Custom sizes from 49 x 85 mm to 55 x 91 mm are available from 38 to 209 gsm. *3: 70 gsm paper.

^{*4:} The scanning speed varies depending on the documents.

Finisher-A2 (Optional)

This ite 712 (Optional)				
Item		Description		
Туре		Sort (Offset available) / Stack (Offset available)		
Paper Size		Max: A3, 11 x 17"; Min: Postcard (100 x 148 mm)		
Paper Weight		60 to 256 gsm		
Paper Capacity*1		[Without Stapling] A4: 500 sheets; JIS B4: 250 sheets; A3 or larger: 200 sheets; Mixed Size Stacking*2: 250 sheets [With Stapling] 30 sets		
	Capacity	A4: 50 sheets (90 gsm or less), JIS B4 or larger: 30 sheets (90 gsm or less)		
Staple	Paper Size	Max: A3, 11 x 17"; Min: JIS B5 LEF		
	Paper Weight	60 to 256 gsm		
	Position	Single stapling, Dual stapling		
Dimensions*3 / Weight		W 658 x D 461 x H 238 mm / W 25.9 x D 18.2 x H 9.4" 11 kg / 25lb		

^{*1: 70} gsm paper.
*2: When larger size sheets are stacked on top of smaller size sheets.
*3: Width 478 mm when the paper support is stored.

Notes
1) If the storage media (such as hard disk drives) of the base unit fail, loss of received data, accumulated data, registered setting data, etc. may occur. In no event shall "the company" be liable for any damages whatsoever arising from loss of data.
2) Functional spare parts will be available for at least 7 years after the product is no longer manufactured.

Hardware configuration

Various combinations



Standard Configuration 1 Tray

Standard Tray

• 520 sheets capacity tray x 1-tary



With 1 Tray Module

With 1 Tray Module
• 520 sheets capacity tray x 2-tray



With 3 Tray Module

With 3 Tray Module
• 520 sheets capacity tray x 4-tray

Standard configuration

- 1. Duplex Automatic Document Feeder
- 130 sheets capacity
- Scan Speed:
- (1 sided scanning) B/W: 80ppm, Color: 80ppm (2 sided scanning) B/W: 80ppm, Color: 80ppm



2. Exit 2 Tray

2 ways output tray Allows to separate the print output each copy, fax and print iob

Finishing option



3. Finisher-A2
• Single stapling, Dual stapling





For Your Safety

Before using the product, read the Instruction Manual carefully for proper use. Use the product
with the power source and voltage specified. Be sure to establish ground connection.
Otherwise, electronic shock may result in the case of a failure or short circuit.

FUJ!FILM

Manufacture

FUJIFILM Business Innovation Corp.

Headquarters

9-7-3, Akasaka Minato-ku, Tokyo 107-0052

TEL: +81-3-6271-5111

fujifilm.com/fbglobal

Distributor

Fujifilm India Private Limited

Unitech Cyber Park, Unit No. 801-807,8th Floor, Tower C, Sector 39, Gurugram- 122001, Haryana, India TEL:+91-(0)124-4325500 The available model varies depending on the country/region. Please ask the sales representatives for details.

The product specifications, appearance and other details in this brochure are subject to change without notice for improvements.

Reproduction Prohibitions Please note that reproduction of the following is prohibited by law:

Domestic and foreign currencies, government-issued securities, and national bonds and local bond
certificates. Thused postage stamps, post cards, etc. -Certificate stamps stipulated by law. -Reproducing
works forming the subject matter of copyright (literary works, musical works, paintings, engravings,
maps, cinematographic works, drawings, photographic works, etc.) is not permitted unless the
reproduction is for the purpose of personal use, family use or other similar uses within a limited circle.

reproduction is for the purpose of personal use, family use or other similar uses within a limited circle. Trademarks - FUIJIEILM and FUIJIEILM log oar registered trademarks of trademarks of FUIJIEILM Corporation - Apeos is registered trademark or trademark of FUIJIEILM Business Innovation Corp. - Adobe, Adobe logo, PostScript and PostScript log oa re either registered trademarks or trademarks of Adobe in the United States and/or other countries - Apple, Mac, macOS, OS X and AirPrint are trademarks of Apple inc. registered in the U.S. and other countries and regions. Morpin, the Mopria Logo, and the Mopria Alliance word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. - All product names and company names mentioned in this brochure are trademarks or registered trademarks of their respective companies.

Authorized Distributor: